

# SMART3G-C2

## with infrared sensor

SMART3G-C2 gas detector is designed to meet industrial requirements; the enclosure is explosion proof and can be installed in ATEX Zone 1 and, when equipped with dust adapter, in Zone 21. The sensing element is placed in the stainless steel head with a 48 mm diameter. The infrared sensors employed for the flammable and refrigerant gas detection are poison free, with high accuracy and a long lifetime. The gas detector has a 12-24 Vdc power supply and a standard 4-20 mA 3-wires output. Optionally, the SMART3G-C2 can be equipped with serial RS485 communication and a 1 or 3 relays board.

The aluminium enclosure has dimensions 120 x 184 x 90 mm, with 3 cable entries 3/4" NPT threaded.

The gas detector can be ATEX marked as following:

CE 0722 Ex II 2G Ex db IIC T5 Gb

Or, when equipped with dust adapter:

CE 0722 Ex II 2GD Ex db IIC T5 Gb  
Ex tb IIIC T5 T100°C Db  
IP65

The gas detector is IECEx compliant and can be marked as following:

II 2G Ex db IIC T5 Gb

Or, when equipped with dust adapter:

II 2GD Ex db IIC T5 Gb  
Ex tb IIIC T5 T100°C Db  
IP65

SMART3G-C2 is SIL2 hardware and SIL3 software; with a redundant system also the hardware is SIL3.



### Sensor

Application	Industrial area, ATEX Zone 1 e Zone 21 (when equipped with dust adapter, optional)
Sensing element	Infrared
Predicted sensor lifetime	>5 years
Gas detected	Flammable, refrigerant and CO <sub>2</sub>
Fullscale	0 - 100% LFL flammable gas 0 - 2000 ppm refrigerant gas 0-2%Vol; 0-5%Vol; 0-30%Vol; 0-100%Vol CO <sub>2</sub>

### Electrical data

Power supply	12-24 Vdc
Output	Analogue 4-20 mA output; 1 or 3 relay board (optional); serial RS485 output (optional)
Maximum dissipated power	5.4 W
Relays contact ratings (optional board)	1.0 A at 30 Vdc
Optical indications	-
Acoustic indications	-
Hall effect sensor	-

### Environmental conditions

Storage temperature	-40 / +85°C
Operating temperature	-40 / +60°C *
Operating humidity	20 / 90% RH @40°C *
Operating pressure	80 / 120 kPa *
Air velocity	6 m/s *
Time of response	t <sub>90</sub> < 60 s ; t <sub>50</sub> < 20 s *

\* Data tested with tests described in EN 60079-29-1 standard

### External case

Material	Enclosure: aluminium pressure die-casting with epoxy paint chromating and chemically resistant Sensor head: stainless steel
Protection mode	Ex d : Explosion proof enclosure Ex t : Equipment dust ignition protection by enclosure (when equipped with dust adapter, optional)
Dimensions	120 x 184 x 90 mm
Weight	1250 g
Cable entries	3 x 3/4" NPT
IP grade	IP65

### Compliance

EMC	EN 61000-6-3:2007 + A1:2011; EN 50270:2015
ATEX	ATEX directive 2014/34/UE EN IEC 60079-0:2018 EN 60079-1:2014 EN 60079-31:2014 EN 60079-29-1:2016
IECEX	IEC 60079-0:2011 IEC 60079-1:2014 IEC 60079-31:2013
SIL	EN 61508:2010 Parti 1, 2, 3, 4, 5, 6, 7 EN50402:2017

Sensitron srl works for a constant improvement of its products and reserves the right to change the technical data without notice.

To have the updated product characteristics check on the website [www.sensitron.it](http://www.sensitron.it) or write an e-mail to [sales@sensitron.it](mailto:sales@sensitron.it)

Sensitron srl, Viale della Repubblica 48, Cornaredo (MI) - 20007  
sales@sensitron.it

TEL. +39 0293548155 FAX. +39 0293548089

**Product codes****ATEX code**

Flammable gas detectors 0-100% LFL, 12-24 Vdc			Refrigerant gas detectors 0-2000 ppm, 12-24 Vdc		
S2624ME	Methane (0-100%LFL) gas detector	ST / L / E3 / S2	S3429R1234YF	R1234YF (0-100%LFL) gas detector	ST / L / E3 / S2
S2654BU	Butane (0-100%LFL) gas detector	ST / L / E3 / S2	S3433R1234ZE	R1234ZE (0-100%LFL) gas detector	ST / L / E3 / S3
S2654PR	Propane (0-100%LFL) gas detector	ST / L / E3 / S2	Refrigerant gas detectors 0-2000 ppm, 12-24 Vdc		
S2654GP	LPG (0-100%LFL) gas detector	ST / L / E3 / S2	S3944R32	R32 (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654AT	Acetone (0-100%LFL) gas detector	ST / L / E3 / S2	S3596R134A	R134A (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654BN	Butadiene (0-100%LFL) gas detector	ST / L / E3 / S2	S3599SF6	SF6 (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654CE	Ciclohexane (0-100%LFL) gas detector	ST / L / E3 / S2	S3656R125	R125 (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654DT	Dimethyl ether (0-100%LFL) gas detector	ST / L / E3 / S2	S3657R1234YF	R1234YF (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654EN	Hetane (0-100%LFL) gas detector	ST / L / E3 / S2	S3948R1234ZE	R1234ZE (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654AE	Ethyl acetate (0-100%LFL) gas detector	ST / L / E3 / S2	S3658R404A	R404A (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654ET	Ethyl alcohol (0-100%LFL) gas detector	ST / L / E3 / S2	S3659R407A	R407A (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654EP	Heptane (0-100%LFL) gas detector	ST / L / E3 / S2	S3920R407F	R407F (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654ES	Hexane (0-100%LFL) gas detector	ST / L / E3 / S2	S3923R449A	R449A (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654IB	Isobuaten (0-100%LFL) gas detector	ST / L / E3 / S2	S3660R507	R507 (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654IL	Isobutylene (0-100%LFL) gas detector	ST / L / E3 / S2	S3017R410A	R410A (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654IP	Isopropyl alcohol (0-100%LFL) gas detector	ST / L / E3 / S2	S3952R417A	R417A (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654PE	Penatne (0-100%LFL) gas detector	ST / L / E3 / S2	S3956R448	R448 (0 - 2000 ppm) gas detector	ST / L / E3 / S3
S2654PP	Propylene (0-100%LFL) gas detector	ST / L / E3 / S2	Carbon dioxide gas detectors, 12-24 Vdc		
S2654DE	R152a (0-100%LFL) gas detector	ST / L / E3 / S2	S2651CO2	CO <sub>2</sub> (0-2% Vol) gas detector	ST / L / E3 / S3
S2654R454B	R454B (0-100%LFL) gas detector	ST / L / E3 / S2	S2652CO2	CO <sub>2</sub> (0-5% Vol) gas detector	ST / L / E3 / S3
S3425R32	R32 (0-100%LFL) gas detector	ST / L / E3 / S2	S2445CO2	CO <sub>2</sub> (0-30% Vol) gas detector	ST / L / E3 / S3
			S2630CO2	CO <sub>2</sub> (0-100% Vol) gas detector	ST / L / E3 / S3

**Mechanical drawings**