

SMART 3

Designed for use in non classified areas



SMART 3 R

- Gas detected: flammable, toxic, CO2 and refrigerant
- Sensors: infrared, catalytic, electrochemical cell



SMART 3 NC

- Gas detected: flammable, toxic, CO2
- Sensors: infrared, catalytic, electrochemical cell



SMART 3H LITE

- CO2 and refrigerant
- Sensor: infrared



SMART 3H FM LITE

- CO2 and refrigerant
- Sensor: infrared



SMART 3 R GAS DETECTOR



- Gas detected: flammable, toxic, CO₂ and refrigerant
- Sensors: infrared, catalytic, electrochemical cell
- Output: analogue 4-20mA, RS485, relay 12-24 Voc power supply

On request 90-240 Vac but without 4-20mA output



sensitron

SMART 3 NC GAS DETECTOR



- Gas detected: flammable, toxic, CO2
- Sensors: infrared, catalytic, electrochemical cell
- Output: analogue 4-20mA, RS485, relay

Needs a control unit



sensitron

SMART 3H LITE GAS DETECTOR



- Gas detected: CO2 and refrigerant
 - Sensor: infrared
 - Output: RS485, relay
-

SMART 3H FM LITE GAS DETECTOR



- Gas detected: CO2 and refrigerant
 - Sensor: infrared
 - Output: RS485, relay
 - Non intrusive calibration via magnet
 - 12-24 Vcc or 90-240 Vca power supply
-



sensitron

Gas detection in machinery room

System:

- SMART 3 R



Gas detection in hospital

System:

- SMART 3 NC



sensitron